## Wisconsin Coalition of Four Wheel Drives Trail Safety Checklist

DRIVER: \_\_\_\_\_\_ EVENT / DATE: \_\_\_\_\_\_ VEHICLE: \_\_\_\_\_\_

ITEM	DESCRIPTION	PASS	FAIL
Battery	Must have OEM equivalent or stronger. Battery cannot move and must be secure.		
Brakes	Must have front & rear brakes. Lines must be secured to axle and/or frame. Pedal		
	cannot be spongy or sink to floor. Brakes must have pressure. No excessively		
	dangling brake lines - appear to be susceptible to snagging on trail debris.		
Cargo	All coolers, tools, spare tires, jacks & cargo must be secured / strapped down.		
Event Liability	Every occupant of every vehicle participating in the trail ride must sign the liability		
Waiver Signed	waiver for the event including minors. See host for questions.		
Exhaust	Must have secured muffler. Turbocharged vehicles may use turbo as muffler		
Fire Extinguisher	Required in each vehicle. Type ABC 2lb min. Must be mounted or secured in vehicle. Prefer to be mounted within reach of driver seat.		
First Aid Kit	Each vehicle will carry a first aid kit.		
Insurance	Proof of vehicle liability insurance required – no exceptions. No proof – no participation.		
Leaks	At tech inspection no significant leaks of any fluids are permitted.		
Pack Out	Each vehicle must have a trash bag. All trail trash must be contained and packed		
Garbage	out including cigarette butts. Trail riders are encouraged to pick up any trash they		
	see while stopped on the trails.		
Recovery Gear C	Each vehicle shall be equipped with a rated recovery rope or strap. Should be		
	rated appropriately for the weight of vehicle. No damage shall be present. Screw		
	type rated clevises or soft shackles only. No Pin clevises permitted.		
Roll Bar	Body mounted roll bars must have backing plates at mounting point.		
	Roll bars are required for vehicles with full removable top. (Stock Jeep Sport Cage		
	is acceptable.) Roll cage shall be constructed of appropriate DOM or HREW		
Seat & Seat Belts	Tubing   Seats must be securely mounted. Seat belts are required for all occupants. All		
Seal & Seal Beils	occupants must wear their seat belt at all times while in the vehicle.		
Shoes	No open toed shoes allowed (sandals, flip flops, barefoot, etc).		
Suspension	Must appear safe.		
Tires & Lug nuts	Must have full size spare. Must have all lug nuts installed. URP		
Tow Points	Required front and rear. OEM or stronger. Class III receiver acceptable. Must		
Tow Fonts	appear structurally safe. Must be attached with grade 5 or better, $\frac{1}{2}$ or larger		
	bolts. Under no circumstances is chain allowed for vehicle towing.		
Winch Windows	If equipped, must have tree saver strap in vehicle. Winch to be shown functional		
	forward / reverse. **WINCH REQUIERD ON EA RIG DURING WINTER EVENTS **		
	If present must be operable to properly communicate with spotter in recovery		
	situation. All occupants to always keep arms and legs in the vehicle at all times		
	while moving.		

## No alcohol allowed on the trails at any time. A CB or GMRS radio is highly advised but not required.

## The decision of tech inspectors is final.